

Technical data

PhoneStar 25

Floor weighting board

- For all types of solid and wooden ceilings
- Ecological raw materials - wood and sand
- Easy to install
- Flat panel - no leveling of fillings necessary
- Can be laid floating or glued down
- No waiting times - can be walked on and loaded immediately



Product description

PhoneStar 25 sound insulation panels are made of environmentally friendly materials - corrugated cardboard and quartz sand - and are approved for use on floors in ETA 20/0371.

Technical data		
Length	0.875 yd	
Width	0.656 yd	
Thickness	0.98 inch	
Weight	97.4 lb/sqyd ± 5.2 lb/sqyd	
Reaction to fire	E	DIN EN 13501
Area load	1.34 klb /sqyd	DIN EN 1991-1-1NA
Point load	0.9 klb	DIN EN 1991-1-1NA
Thermal conductivity	1.18 BTU·in/h·ft²·°F	DIN EN 12664
Application	Interior fittings	

Storage:

- Only store PhoneStar boards indoors, flat, dry and frost-free.
- Store at the installation site for 24 hours to acclimatize.
- Protect edges from damage.

GREENMODUL DISTRIBUTION · Greenmodul Sp.zoo, Ul.Grzybowska 80/82, 00-844 Warszawa, Phone: + 48 663 199 008, +48 883 380 540, + 48 518 532 958, contact@greenmodulcanada.com, gk@greenmodulcanada.com.

We guarantee the consistent quality of our products, but reserve the right to make technical changes and further developments. The information on this data sheet is based on practical and scientific experience and corresponds to the manufacturer's specifications. As we have no influence on the variety of materials or their processing, we cannot assume any guarantee of properties in the sense of the latest BGH case law. This information is of a non-binding nature and does not exempt you from carrying out sufficient tests yourself.